402/502 Series

All Stainless Steel Extreme High Pressure Gauges

The Challenge

Backed by our extended warranty, NOSHOK 402/502 Series corrosion-resistant dry or liquid-filled gauge Extreme High Pressure Gauges are in compliance with the new DIN 16001 standard, which specifically addresses extreme high pressure ranges starting at 30,000 psi.

These gauges exceeded the minimum requirements of the specification by more than 20 times in our qualification cycle testing. Ideal for applications including pumps & compressors, high pressure processing, test equipment & systems and waterjet cutting.

NOSHOK 402/502 Series Extreme High Pressure Gauges Features Include:

- Corrosion-resistant dry or liquid-filled gauge for high pressure applications
- Ranges from 0 psi to 30,000 psi through 0 psi to 85,000 psi
- 4” to 6” gauge sizes
- Solid front design with a blow out back in accordance to EN 837, S3 Safety Pattern
- Stainless Steel case
- NiFe alloy/316L Stainless Steel wetted parts
- DIN 16001 compliant

NOSHOK 402/502 Series Extreme High Pressure Gauges Benefits Include:

- Improved load cycle stability
- Improved calibrations stability
- Significantly longer service life
- Reduced down time





These features combine to provide higher safety levels, improved reliability and reduced maintenance costs, resulting in a lower total cost of ownership.